



Husky SD 4000 Coupling

The Husky SD 4000 Coupling is a super-duty, all-stainless-steel pipe coupling designed to securely join No-Hub cast iron soil piping. Manufactured with a wider shield (304 Stainless steel) and extra clamps to distribute load and reduce joint movement for extra rigidity.

It features a robust corrugated shield and multiple sealing clamps to ensure a rigid and leak-resistant joint. The high-purity neoprene gasket has a double sealing zone, withstands high liquid temperatures up to 100°C/212°F and does not support flame.

Size	Qty / Box	Α	В
1 ½ × 1 ½	60	2 ¼	3
38 × 38		57	76
2 × 2	75	2¾	3
50 × 50		70	76
3 × 3	48	3¾	3
75 × 75		95	76
4 × 4	48	4¾	3
100 × 100		121	76
5 × 5	15	5¾	4
125 × 125		146	102
6 × 6	15	6¾	4
150 × 150		171	102
8 × 8	15	8¾	4
200 × 200		222	102
10 × 10	12	10¾	4
250 × 250		273	102








No-hub couplings are available in sizes from $1 \ensuremath{1}\!\!\!/_2$ " to 15" in diameter.

Certified to CSA B70 & B602 and listed to CAN/ULC S-102.2-10







Intertek

The clamp bands require 80 in-lbs. of torque. The proper sealing sequence must be followed.